

# COLLOM | COLLOM DOUBLE



## COLLOM

Material	steel pipes $\varnothing$ 28 mm / steel profiles 70 × 11 mm
Connection thread	2 × G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of profiles	4, 6, 8

## COLLOM DOUBLE

Material	steel pipes $\varnothing$ 28 mm / steel profiles 70 × 11 mm
Connection thread	2 × G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of profiles	8, 12, 16



COLLOM DOUBLE 1800 × 602

## COLLOM

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input paint [W]	Recommended power input chrome [W]	Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C			
1800/298	39	14,0	4,1	1,272	614	499	321	-	-	mc 50
1800/450	39	21,0	6,1	1,272	910	740	475	-	-	mc 50
1800/602	39	27,5	7,9	1,272	1205	943	602	-	-	mc 50

## COLLOM DOUBLE

Type H/L [mm]	Depth B1 [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input paint [W]	Recommended power input chrome [W]	Connection span [mm]
					75/65/20 °C	70/55/20 °C	55/45/20 °C			
1800/298	48	28,3	7,9	1,304	817	661	420	-	-	mc 50
1800/450	48	42,3	11,9	1,304	1162	940	597	-	-	mc 50
1800/602	48	56,4	15,9	1,288	1549	980	629	-	-	mc 50

Thermal power measuring follows in accordance with EN 442.

Collom Double Mirror is available per order.

Accessories (page 64, 65 and 66) is not part of the radiator.

