

# ANTIKA LIGHT | ANTIKA DOUBLE



## ANTIKA LIGHT

Material	steel pipes $\varnothing$ 28 mm / steel profiles 50 × 10 mm
Connection thread	4 × G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of profiles	8, 13, 17

## ANTIKA DOUBLE

Material	steel pipes $\varnothing$ 28 mm / steel profiles 50 × 10 mm
Connection thread	4 × G1/2"
Testing overpressure	0,65 MPa
Max. operating overpressure	0,5 MPa
Max. operating temperature	110 °C
Number of profiles	16, 26, 34



ANTIKA DOUBLE 1800 × 600


## ANTIKA LIGHT

Type H/L [mm]	Depth B [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input paint [W]	Recommended power input chrome [W]	Connection span [mm]
					75/65/20°C	70/55/20°C	55/45/20°C			
1800/300	79	19,5	4,9	1,292	821	666	424	-	-	mc 50
1800/480	79	31,0	8,1	1,292	1314	1065	679	-	-	mc 50
1800/600	79	40,5	10,5	1,292	1643	1332	849	-	-	mc 50

## ANTIKA DOUBLE

Type H/L [mm]	Depth B1 [mm]	Weight [kg]	Water capacity [l]	Temperature exponent [n]	Heating Output [W]			Recommended power input paint [W]	Recommended power input chrome [W]	Connection span [mm]
					75/65/20°C	70/55/20°C	55/45/20°C			
1800/300	128	37,5	9,7	1,262	1127	918	592	-	-	mc 50
1800/480	128	60,5	15,8	1,262	1793	1461	941	-	-	mc 50
1800/600	128	79,0	20,7	1,262	2325	1894	1221	-	-	mc 50

Thermal power measuring follows in accordance with EN 442.  
Accessories (page 64, 65 and 66) is not part of the radiator.



Connection options

